




Upset Drill Pipe Tubing

1.900" X 3.64 lb/ft TPS Multiseal TS-8

UPSET DRILL PIPE TUBING

1.900" X 3.64 lb/ft TPS Multiseal TS-8



Specification	
OEM	TPS Technitube
Country of Origin	Germany
Nominal Tubing OD	1.900"
Drift Size	1.286"
Steel Grade	L-80
Nominal Weight	3.64 lb/ft
Nominal Wall Thickness	0.200"
Nominal ID	1.500"
Connection Length	(LP -Length Pin) (LB – Length Box) LB Minimum = LP – 0.21"
Connection Make Up Loss	2.23"
Manufacturing Criteria	API 5CT

Tubing Capacities		
Body Yield Strength	85,000 lbs	379 kN
API Collapse	15,070 psi	1039 bar
Internal Yield	14,740 psi	1017 bar
Joint Strength	86,000 lbs	383 kN

Connection Specifications			
Connection	TPS MULTISEAL TS-8	Compatible With	1 1/2" Hyd CS
OD	2.162"	ID	1.440"
Connection Length	2.43"	Minimum	
	3.27"	Standard	1 recut
	4.11"	Type 2	2 recut
	4.95"	Type 3	3 recut
Minimum Make Up Torque	800 lb/ft	1085 N m	
Optimum Make Up Torque	900 lb/ft	1220 N m	
Maximum Make Up Torque	1000 lb/ft	1360 N m	
Connection Tensile Efficiency	101.3%	Inspection Criteria	API 5A5, API 5CT

The information on this specification sheet is provided for illustration purposes only and is taken from information available from the manufacturer and other public sources. Saltire Energy Limited accepts no responsibility or liability for the accuracy of the information provided or for any error, omission or misstatement.

Our Locations

SALTIRE ENERGY HUB

Badentoy Crescent, Portlethen

Aberdeen, AB12 4YD

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

FAR EAST

No.20 Tuas Ave 10, Singapore, 639144

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

MIDDLE EAST

Musaffah, Abu Dhabi, 53161

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

NORWAY

Hamrasletta 5, 4056 Tanager, Stavanger

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541



www.saltire-energy.com