



**TenarisHydril TSHW511 Flush Joint Tubing**

**4.000" X 9.50 lb/ft**

# DRILL PIPE TUBING

## 4.000" X 9.50 lb/ft TenarisHydril TSHW511 Flush Joint Tubing



 Tenaris

Specification	
OEM	TenarisHydril
Country of Origin	UK, Romania, Argentina
Nominal Tubing OD	4" (4.00")
Drift Size	3.423"
Steel Grade	L-80
Nominal Weight	9.50 lb/ft
Nominal Wall Thickness	0.226"
Nominal ID	3.548"
Connection Length	
Connection Make Up Loss	2.740"
Manufacturing Criteria	API 5CT

Tubing Capacities		
Body Yield Strength	214,000 lbs	952 kN
API Collapse	6,590 psi	470 bar
Internal Yield	7,910 psi	545 bar
Joint strength	132,000 lbs	588 kN

Connection Specifications			
Connection	4" TSHW511	Compatible With	
OD	4.000"	ID	3.454"
Connection Length	Minimum		
	Standard	1 recut	
	Type 2	2 recut	
	Type 3	3 recut	
Minimum Make Up Torque	1,300 lb/ft	1757 N m	
Optimum Make Up Torque	1,600 lb/ft	2162 N m	
Maximum Make Up Torque	2,300 lb/ft	2838 N m	
Connection Tensile Efficiency	61.8%	Inspection Criteria	API 5A5, API 5CT

The information on this specification sheet is provided for illustration purposes only and is taken from information available from the manufacturer and other public sources. Saltire Energy Limited accepts no responsibility or liability for the accuracy of the information provided or for any error, omission or misstatement.

# Our Locations

## SALTIRE ENERGY HUB

Badentoy Crescent, Portlethen

Aberdeen, AB12 4YD

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541

## FAR EAST

No.20 Tuas Ave 10, Singapore, 639144

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541

## MIDDLE EAST

Musaffah, Abu Dhabi, 53161

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541

## NORWAY

Hamrasletta 5, 4056 Tanager, Stavanger

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541



[www.saltire-energy.com](http://www.saltire-energy.com)