



TenarisHydril PH4 Integral Upset Tubing

4.500" X 24.0 lb/ft

UPSET DRILL PIPE TUBING

4.500" X 24.0 lb/ft TenarisHydril PH4



Specification	
OEM	TPS Techniseal & TenarisHydril
Country of Origin	Germany
Nominal Tubing OD	4 ½" (4.500")
Drift Size	3.255"
Steel Grade	C-95SS
Nominal Weight	24.0 lb/ft
Nominal Wall Thickness	0.560"
Nominal ID	3.380"
Connection Length	
Connection Make Up Loss	4.76"
Manufacturing Criteria	API 5CT

Tubing Capacities		
Body Yield Strength	659,000 lbs	2900 kN
API Collapse	20,700 psi	1427 bar
Internal Yield	20.690psi	1427 bar
Joint Strength	659,000 lbs	2900 kN

Connection Specifications			
Connection	TenarisHydril PH-4	Compatible With	
OD	5.563"	ID	3.300"
		Minimum	
		Standard	1 recut
		Type 2	2 recut
		Type 3	3 recut
Minimum Make Up Torque	11,800 lb/ft	15946 N m	
Optimum Make Up Torque	13,300 lb/ft	17973 N m	
Maximum Make Up Torque	14,800 lb/ft	20000 N m	
Connection Tensile Efficiency	100%	Inspection Criteria	API 5A5, API 5CT

The information on this specification sheet is provided for illustration purposes only and is taken from information available from the manufacturer and other public sources. Saltire Energy Limited accepts no responsibility or liability for the accuracy of the information provided or for any error, omission or misstatement.

Our Locations

SALTIRE ENERGY HUB

Badentoy Crescent, Portlethen

Aberdeen, AB12 4YD

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

FAR EAST

No.20 Tuas Ave 10, Singapore, 639144

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

MIDDLE EAST

Musaffah, Abu Dhabi, 53161

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

NORWAY

Hamrasletta 5, 4056 Tanager, Stavanger

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541



www.saltire-energy.com