NOV Grant Prideco Drill Pipe

5.000” x 19.50 lb/ft XT50 Range 2

NOV Grant Prideco Drill Pipe

5.000” x 19.50 lb/ft XT50 Range 2

Specification	
OEM	NOV Grant Prideco
Country of Origin	USA
Nominal OD	5” (5.000”)
Nominal ID	
Steel Grade	S-135
Nominal Weight	19.50#
Nominal Wall Thickness	0.362”
Drift Size	3.625”
Hardbanding	
IPC	
Pin Length	12”
Box Length	17”
Average Weight Per Joint	
Manufacturing Criteria	
Pipe Body Capacities	
Yield Strength	
API Collapse	15,672 psi / 10,029 psi
Torsional Yield Strength	74,000 lb/ft / Premium 58,100 lb/ft
Pipe Burst Resistance	17,105 psi / Premium 15,638 psi

Tool Joint / Connection Specifications			
Connection	XT50	Compatible With	
OD	6 1/2” (6.500”)	ID	3 3/4” (3.750”)
Adjusted Weight	23.74 lb/ft	Average Length	Min 31.0ft – Max 32.0ft
Tensile Yield		Torsional Yield	
Minimum Make Up Torque	38,500 lb/ft	Maximum Make Up Torque	46,100 lb/ft
Fluid Displacement	0.37 gal/ft	Fluid Capacity	0.72 gal/ft
Type of Upset	IEU	Inspection Criteria	

The information on this specification sheet is provided for illustration purposes only and is taken from information available from the manufacturer and other public sources. Saltire Energy Limited accepts no responsibility or liability for the accuracy of the information provided or for any error, omission or misstatement.

Our Locations

SALTIRE ENERGY HUB

Badentoy Cresent, Portlethen

Aberdeen, AB12 4YD

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

FAR EAST

No.20 Tuas Ave 10, Singapore, 639144

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

MIDDLE EAST

Musaffah, Abu Dhabi, 53161

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

NORWAY

Hamrasletta 5, 4056 Tanager, Stavanger

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

Saltire energy

www.saltire-energy.com