OMSCO Heavyweight Drill Pipe

5.000” X Welded HWDP NC50 Range 2

OMSCO Heavyweight Drill Pipe

5.000” X Welded HWDP NC50 Range 2



Specification	
OEM	OMSCO
Country of Origin	USA
Nominal OD	5” (5.000”)
Nominal ID	3” (3.000”)
Steel Grade	AISI 4130
Nominal Weight	50.00#
Nominal Wall Thickness	1” (1.000”)
Drift Size	2 7/8” (2.875”)
Hardbanding	Arnco 100XT
Hardbanding Center Wear Band	O-1000
Pin Length	24”
Box Length	24”
Average Weight Per Joint	1,721 lbs (782 kgs)
Manufacturing Criteria	API Spec 7-1 /NS-1
Pipe Body Capacities	
Yield Strength	817,000 lbs
API Collapse	20,800 psi
Torsional Yield Strength	66,800 lb/ft
Pipe Burst Resistance	26,000 psi

Tool Joint / Connection Specifications			
Connection	NC50	**Compatible With**	NC50 DSTJ GPDS 50
OD	6 1/2” (6.500”)	**ID**	3 1/16” (3.063”)
Type of Tool Joint	Welded	**414 H Mod**	
Adjusted Weight	56.19 lb/ft	**Average Length**	31.0 ft
Tensile Yield	1,380,000 lbs	**Torsional Yield**	56,000 ft/lbs
Make Up Torque	33,600 lb/ft		
Centre Upset OD	5 1/2” (5.500”)	**Fluid Capacity**	0.37 gal/ft
Type of Upset		**Inspection Criteria**	NS-2

The information on this specification sheet is provided for illustration purposes only and is taken from information available from the manufacturer and other public sources. Saltire Energy Limited accepts no responsibility or liability for the accuracy of the information provided or for any error, omission or misstatement.

Our Locations

SALTIRE ENERGY HUB

Badentoy Cresent, Portlethen

Aberdeen, AB12 4YD

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

FAR EAST

No.20 Tuas Ave 10, Singapore, 639144

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

MIDDLE EAST

Musaffah, Abu Dhabi, 53161

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

NORWAY

Hamrasletta 5, 4056 Tanager, Stavanger

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

Saltire energy

www.saltire-energy.com