



**NOV Grant Prideco Drill Pipe**

**5.500" TT550 Range 2**

# NOV Grant Prideco Drill Pipe

## 5.500” TT550 Range 2

Specification	
OEM	NOV Grant Prideco
Country of Origin	USA
Nominal OD	5 1/2” (5.500”)
Nominal ID	4.250”
Steel Grade	S-135
Nominal Weight	21.90#
Nominal Wall Thickness	0.361”
Drift Size	4.125”
Hardbanding	
IPC	
Pin Length	12”
Box Length	17”
Average Weight Per Joint	
Manufacturing Criteria	
Pipe Body Capacities	
Yield Strength	
API Collapse	12,679 psi
Torsional Yield Strength	91,300 lb/ft
Pipe Burst Resistance	15,507 psi

Tool Joint / Connection Specifications			
Connection	Turbo Torque 550	Compatible With	
OD	6.625”	ID	4.250”
Adjusted Weight		Average Length	Min 31.0ft – Max 32.0ft
Tensile Yield	130,000 lbs	Torsional Yield	84,600 ft/lbs
Minimum Make Up Torque	42,400 lb/ft	Maximum Make Up Torque	
Fluid Displacement	0.39 gal/ft	Fluid Capacity	0.9 gal/ft
Type of Upset	IEU	Inspection Criteria	

The information on this specification sheet is provided for illustration purposes only and is taken from information available from the manufacturer and other public sources. Saltire Energy Limited accepts no responsibility or liability for the accuracy of the information provided or for any error, omission or misstatement.

# Our Locations

## **SALTIRE ENERGY HUB**

Badentoy Crescent, Portlethen

Aberdeen, AB12 4YD

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541

## **FAR EAST**

No.20 Tuas Ave 10, Singapore, 639144

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541

## **MIDDLE EAST**

Musaffah, Abu Dhabi, 53161

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541

## **NORWAY**

Hamrasletta 5, 4056 Tanager, Stavanger

[enquiries@saltire-energy.com](mailto:enquiries@saltire-energy.com)

+44 (0)1224 872228

+44 (0)1224 897541



[www.saltire-energy.com](http://www.saltire-energy.com)