Saltire energy

NOV Grant Prideco Drill Pipe

5.875” x 23.40 lb/ft XT57 Range 2

NOV Grant Prideco Drill Pipe

5.875” x 23.40 lb/ft XT57 Range 2

Specification	
OEM	NOV Grant Prideco
Country of Origin	USA
Nominal OD	5 7/8” (5.875”) / Premium 5.731”
Nominal ID	5.153” / Premium 5.153”
Steel Grade	S-135
Nominal Weight	23.40#
Nominal Wall Thickness	0.361”
Drift Size	4.125”
Hardbanding	TCS-Ti
IPC	TK34P
Pin Length	12”
Box Length	17”
Average Weight Per Joint	850 lbs (387 kgs)
Manufacturing Criteria	API Spec 5DP(PSL1) / NS-1
Pipe Body Capacities	
Yield Strength	844,200 lbs / 666,500 lbs
API Collapse	10,825 psi / 6,204 psi
Torsional Yield Strength	105,500 lb/ft / Premium 83,000 lb/ft
Pipe Burst Resistance	14,517 psi / Premium 13,273 psi

Tool Joint / Connection Specifications			
Connection	XT 57	Compatible With	
OD	7” (7.000”)	ID	4 1/4” (4.250”)
Adjusted Weight	27.00 lb/ft	Average Length	31.0 ft
Tensile Yield	1,208,700 lbs	Torsional Yield	94,300 ft/lbs
Minimum Make Up Torque	33,800 lb/ft	Maximum Make Up Torque	56,600 lb/ft
Fluid Displacement	0.41 gal/ft	Fluid Capacity	1.04 gal/ft
Type of Upset	IEU	Inspection Criteria	NS-2

The information on this specification sheet is provided for illustration purposes only and is taken from information available from the manufacturer and other public sources. Saltire Energy Limited accepts no responsibility or liability for the accuracy of the information provided or for any error, omission or misstatement.

Our Locations

SALTIRE ENERGY HUB

Badentoy Cresent, Portlethen

Aberdeen, AB12 4YD

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

FAR EAST

No.20 Tuas Ave 10, Singapore, 639144

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

MIDDLE EAST

Musaffah, Abu Dhabi, 53161

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

NORWAY

Hamrasletta 5, 4056 Tanager, Stavanger

enquiries@saltire-energy.com

+44 (0)1224 872228

+44 (0)1224 897541

Saltire energy

www.saltire-energy.com